

IN THE CLAIMS:

1. (Previously Amended) A display device comprising:
a display panel comprising a pixel portion in which a plurality of thin film transistors are arranged in a matrix, a digital video signal dividing circuit, a source driver circuit, and a gate driver circuit;
an image signal processing circuit for processing an image signal input from an external source; and
a control circuit which feeds pulses to said display panel and said image signal processing circuit,
wherein said image signal processing circuit corrects said image signal on a basis of a correction table and feeds said digital video signal dividing circuit with said corrected image signal.
2. (Previously Amended) A display device according to claim 1, wherein said display panel is a liquid crystal display panel.
3. (Original) A display device according to claim 1, wherein said source driver circuit is a digital driver with a D/A conversion circuit.
4. (Original) A display device according to claim 1, wherein said image signal processing circuit comprises a correction circuit and an A/D conversion circuit.
5. (Original) A display device according to claim 1, wherein said display device is one selected from the group consisting of a projector, a goggle type display, a mobile computer, a video camera, a DVD player, and a game machine.
6. (Previously Amended) A display device comprising:
a display panel comprising a pixel portion in which a plurality of thin film transistors are arranged in a matrix, a digital video signal dividing circuit, a source driver circuit, and a gate driver circuit;
an image signal processing circuit for processing an image signal input from an

external source; and

a control circuit which feeds pulses to said display panel and said image signal processing circuit,

wherein said image signal processing circuit performs gamma correction on said image signal on a basis of a correction table and feeds said digital video signal dividing circuit with said image signal on which gamma correction has been performed.

7. (Original) A display device according to claim 6, wherein said display panel is a liquid crystal display panel.

8. (Original) A display device according to claim 6, wherein said source driver circuit is a digital driver with a D/A conversion circuit.

9. (Original) A display device according to claim 6, wherein said image signal processing circuit comprises a correction circuit and an A/D conversion circuit.

10. (Original) A display device according to claim 6, wherein said display device is one selected from the group consisting of a projector, a goggle type display, a mobile computer, a video camera, a DVD player, and a game machine.

11. (Previously Amended) A method for operating a display device comprising the steps of:

processing an image signal input from an external source by an image signal processing circuit;

feeding pulses to said image signal processing circuit and a display panel by a control circuit, wherein the display panel comprises a pixel portion in which a plurality of thin film transistors are arranged in a matrix, a digital video signal dividing circuit, a source driver circuit, and a gate driver circuit;

correcting said image signal based on a correction table; and

feeding a corrected image signal to said digital video signal dividing circuit

through a correction circuit.

12. (Original) A method according to claim 11, wherein said display device is a liquid crystal display device.

13. (Original) A method according to claim 11, wherein said display device is one selected from the group consisting of a projector, a goggle type display, a mobile computer, a video camera, a DVD player, and a game machine.

14. (Previously Amended) A method for operating a display device comprising the steps of:

processing an image signal input from an external source by an image signal processing circuit;

feeding pulses to said image signal processing circuit and a display panel by a control circuit, wherein the display panel comprises a pixel portion in which a plurality of thin film transistors are arranged in a matrix, a digital video signal dividing circuit, a source driver circuit, and a gate driver circuit;

performing a gamma correction of said image signal based on a correction table; and

feeding a corrected image signal to said digital video signal dividing circuit through a correction circuit.

15. (Original) A method according to claim 14, wherein said display device is a liquid crystal display device.

16. (Original) A method according to claim 14, wherein said display device is one selected from the group consisting of a projector, a goggle type display, a mobile computer, a video camera, a DVD player, and a game machine.

17. (Previously Amended) A display device comprising:
a display panel comprising a pixel portion in which a plurality of thin film

transistors are arranged in a matrix, a digital video signal dividing circuit, a source driver circuit, and a gate driver circuit, wherein each circuit is formed over a same substrate as said pixel portion;

an image signal processing circuit for processing an image signal input from an external source; and

a control circuit which feeds pulses to said display panel and said image signal processing circuit,

wherein said image signal processing circuit corrects said image signal on a basis of a correction table and feeds said digital video signal dividing circuit with said corrected image signal.

18. (Previously Amended) A display device according to claim 17, wherein said display panel is a liquid crystal display panel.

19. (Original) A display device according to claim 17, wherein said source driver circuit is a digital driver with a D/A conversion circuit.

20. (Original) A display device according to claim 17, wherein said image signal processing circuit comprises a correction circuit and an A/D conversion circuit.

21. (Original) A display device according to claim 17, wherein said display device is one selected from the group consisting of a projector, a goggle type display, a mobile computer, a video camera, a DVD player, and a game machine.

22. (Previously Amended) A display device comprising:

a display panel comprising a pixel portion in which a plurality of thin film transistors are arranged in a matrix, a digital video signal dividing circuit, a source driver circuit, and a gate driver circuit, wherein each circuit is formed over a same substrate as said pixel portion;

an image signal processing circuit for processing an image signal input from an external source; and

a control circuit which feeds pulses to said display panel and said image signal processing circuit,

wherein said image signal processing circuit performs gamma correction on said image signal on a basis of a correction table and feeds said digital video signal dividing circuit with said image signal on which gamma correction has been performed.

23. (Original) A display device according to claim 22, wherein said display panel is a liquid crystal display panel.

24. (Original) A display device according to claim 22, wherein said source driver circuit is a digital driver with a D/A conversion circuit.

25. (Original) A display device according to claim 22, wherein said image signal processing circuit comprises a correction circuit and an A/D conversion circuit.

26. (Original) A display device according to claim 22, wherein said display device is one selected from the group consisting of a projector, a goggle type display, a mobile computer, a video camera, a DVD player, and a game machine.

27. (Original) A display device according to claim 1, wherein said pulses comprises at least one selected from the group consisting of a start pulse, a clock pulse, and a synchronizing signal.

28. (Original) A display device according to claim 6, wherein said pulses comprises at least one selected from the group consisting of a start pulse, a clock pulse, and a synchronizing signal.

29. (Original) A method according to claim 11, wherein said pulses comprises at least one selected from the group consisting of a start pulse, a clock pulse, and a synchronizing signal.

30. (Original) A method according to claim 14, wherein said pulses comprises at least one selected from the group consisting of a start pulse, a clock pulse, and a synchronizing signal.

31. (Original) A display device according to claim 17, wherein said pulses comprises at least one selected from the group consisting of a start pulse, a clock pulse, and a synchronizing signal.

32. (Original) A display device according to claim 22, wherein said pulses comprises at least one selected from the group consisting of a start pulse, a clock pulse, and a synchronizing signal.